



14	SAFETY VALVE
13	RATING PLATE
12	PORCELAIN BUSHING 1/2000A EN50386 + FLAG DIN43675
11	POCKET WELL 1" G
10	PLUG-IN BUSHING 24/250A INTERFACE "A" EN50180
9	ORTHOGONAL POSITIONED WHEELS Ø160
8	OIL THERMOMETER MAIER MBTC-16 2 CE CO 1" MT21063
7	OFF LOAD TAP CHANGER "A"
6	OFF LOAD TAP CHANGER
5	M10x55
4	LIFTING LUGS
3	FILLING TUBE
2	EARTH CONNECTION M12 DIN48088
1	DRAIN VALVE DIN42551
pos	description

0 28/06/2023
REV DATE

GBE S.p.A. reserves property rights to this drawing to all legal effects

DESCRIPTION		EMITTED BY	CHECKED BY	APPROVED BY
OIL FILLED TRANSFORMER LAYOUT 1250 kVA		Piovan	Arzenton	Vencato
Material		Weight	GBE Serial N°	
		3260 kg (+5-10% tol.)	20528	
Description			Status	Drawing N°
			FOR PRODUCTION	A25620
GBE Code			Scale	Sheet
ER3024.1250			1:15	1 / 1
WHERE NOT INDICATED TOLERANCES REFER TO UNI EN 22768 MEDIUM GRADE			Sheet Size	Sheet
			A3	1 / 1

MV Voltage regulation		Rating power	1250 kVA
position	step	Frequency	50 Hz
1	++	Voltages (no load)	22(11) +2 / -4 x 2,5% / 0,415 kV
2	+		
3	0		
MV Tap changer "A"		Group	Dyn11
position	[kV]	Final shade	RAL7033 C3
II	22	Oil weight	635 kg
I	11		